

MONTANA WELL LOG REPORT

Form No. 603 P2-04

Well ID# _____

This log reports the activities of a licensed Montana well driller and serves as the official record of work done within the borehole and casing and describes the amount of water encountered. This form is to be completed by the driller and filed with MBRG within 60 days of completion of the work. Acquiring Water Rights is the well owner's responsibility and is not accomplished by the filing of this report.

Well-log information is stored in the Groundwater Information Center at the Montana Bureau of Mines and Geology (Butte) and water right information is stored in the Water Rights Bureau records (Helena).

For fields that are not applicable, enter NA.

Record additional information in the REMARKS section.

1. WELL OWNER:

Name John RichardsMailing address Box 316Seeley Lake MT 59868

2. WELL LOCATION: List ¼ from smallest to largest

Section 5Township 14 N Range 14 E County Missoula3. PROPOSED USE: Domestic Stock Irrigation Public water supply Monitoring Well Other:

4. TYPE OF WORK:

 New well Deepen existing well Abandon existing wellMethod: Cable Rotary Other:

5. WELL CONSTRUCTION DETAILS:

Borehole:

Dia. 6 in. from BS ft. to 40 ft.Dia. in. from ft. to ft.Dia. in. from ft. to ft.

Casing:

Steel: Wall thickness .250 Threaded WeldedDia. 6 in. from 43 ft. to 40 ft.Dia. in. from ft. to ft.Plastic: Pressure Rating lbs. Threaded WeldedDia. in. from ft. to ft.

Perforations/Botted Pipe:

Type of perforator used HolecSize of perforations/slots 10' in. by 1" in.no. of perforations/slots from 25 ft. to 35 ft.no. of perforations/slots from ft. to ft.

Screening:

 Yes NoMaterial Dia. Slot size from ft. to ft.Dia. Slot size from ft. to ft.

Gravel packed:

 Yes NoSize of gravel Gravel placed from ft. to ft.

Packer:

 Yes NoType Depth(s)

Grout:

Material used BentoniteDepth from ft. to ft. OR Continuous feed

WELL TEST DATA:

A well test is required for all wells. (See details on well log report cover.)

 Static water level 7 ft. below top of casing or Closed-in artesian pressure psi.

How was test flow measured:

bucket/topwatch, weir, flume, flowmeter, etcInstructor Controlled Groundwater Area - Water Temperature 70° F AQUIFER TEST DATA FORM ATTACHED

Test - 1 hour minimum

Drawdown is the amount water level is lowered below static level.

All depth measurements shall be from the top of the well casing.

Time of recovery is hours/minutes since pumping stopped.

Air test: 30 gpm with drill stem set at 35 ft. for 3 hoursTime of recovery 5 hrs/min. Recovery water level 2 ft.

OR Bell test*

gpm with ft. of drawdown after hoursTime of recovery hrs/min. Recovery water level ft.

OR Pump test*

Depth pump set for test ft.gpm pump rate with ft. of drawdown after hrs pumpingTime of recovery hrs/min. Recovery water level ft.

OR Flowing Artesian*

gpm for hoursFlow controlled by

*During the well test the discharge rate shall be as uniform as possible. This rate may or may not be the sustainable yield of the well. Sustainable yield does not include the reservoir of the well-casing.

7. WELL LOG:

Depth, Feet	Material
0' to 10'	Sand, Gravel, Cobble
10' to 35'	Gravel, Cobbles, Clay w/water
35' to 40'	Clay, Sand
40' to 50'	
50' to 60'	
60' to 70'	
70' to 80'	
80' to 90'	
90' to 100'	
100' to 110'	
110' to 120'	
120' to 130'	
130' to 140'	
140' to 150'	
150' to 160'	
160' to 170'	
170' to 180'	
180' to 190'	
190' to 200'	
200' to 210'	
210' to 220'	
220' to 230'	
230' to 240'	
240' to 250'	
250' to 260'	
260' to 270'	
270' to 280'	
280' to 290'	
290' to 300'	
300' to 310'	
310' to 320'	
320' to 330'	
330' to 340'	
340' to 350'	
350' to 360'	
360' to 370'	
370' to 380'	
380' to 390'	
390' to 400'	
400' to 410'	
410' to 420'	
420' to 430'	
430' to 440'	
440' to 450'	
450' to 460'	
460' to 470'	
470' to 480'	
480' to 490'	
490' to 500'	
500' to 510'	
510' to 520'	
520' to 530'	
530' to 540'	
540' to 550'	
550' to 560'	
560' to 570'	
570' to 580'	
580' to 590'	
590' to 600'	
600' to 610'	
610' to 620'	
620' to 630'	
630' to 640'	
640' to 650'	
650' to 660'	
660' to 670'	
670' to 680'	
680' to 690'	
690' to 700'	
700' to 710'	
710' to 720'	
720' to 730'	
730' to 740'	
740' to 750'	
750' to 760'	
760' to 770'	
770' to 780'	
780' to 790'	
790' to 800'	
800' to 810'	
810' to 820'	
820' to 830'	
830' to 840'	
840' to 850'	
850' to 860'	
860' to 870'	
870' to 880'	
880' to 890'	
890' to 900'	
900' to 910'	
910' to 920'	
920' to 930'	
930' to 940'	
940' to 950'	
950' to 960'	
960' to 970'	
970' to 980'	
980' to 990'	
990' to 1000'	

 ADDITIONAL SHEETS ATTACHED8. DATE WELL COMPLETED: 5/8/07RECORDED BY JEROME'S DRILLING CO.Address Box 12020 Missoula MT 59808Signature Jerome's Drilling Co.Date 5/22/07 License no. 600MBMGID# 4066773400

DNRC COPY