

Customer's Name Low & Mac BARNETT Job No. _____

Overhead Door/Opening Information

Door Height _____ (See Floor Plan)

Set Door _____ " Above Grade.

Headroom Required _____

O.H.D. Panel Width (See Floor Plan) _____

(Note: Opening Width Clearance Will be 2" Less Than Door Width)

GUTTERS		Accessory Colors (fill in applicable boxes)			
DRAIN	VENT-RIDGE	SLIDING DOOR JAMBS	TRACK COVER	SLIDING DOOR RAILS	TOP SLIDING DOOR TRIM
Endwall Overhang Width <u>2'</u>	ALTERNATE RIDGE CAP	WHITE	WHITE	WHITE	WHITE
Sidewall Overhang Width <u>2'</u>	CUPOLA ROOF	SILVER	WHITE	WHITE	WHITE
	CUPOLA SIDES	WHITE	WHITE	WHITE	WHITE
	CABLE TRIM	WHITE	WHITE	WHITE	WHITE
	FASCIA	WHITE	WHITE	WHITE	WHITE
	SOFFIT	WHITE	WHITE	WHITE	WHITE
	CORNER TRIM	WHITE	WHITE	WHITE	WHITE
	GUTTERS	WHITE	WHITE	WHITE	WHITE

OVERHANGS

FOUNDATION OPTIONS

FOUNDATION WALL

MONOLITHIC SLAB

Customer's Signature [Signature]

Date: 02/12/97

One Square Equals 3 Feet

Form 86 6/96

VENTILATORS, INSULATION, AND VAPOR BARRIERS WILL REDUCE BUT NOT ELIMINATE CONDENSATION. SLIDING DOOR OPENINGS WILL BE 4 1/2" TO 7 1/2" LESS IN WIDTH (EXCEPT SLIDING DOORS LOCATED IN SIDEWALL CORNERS MAY BE 10" LESS IN WIDTH) THAN DOOR PANELS AND OPENING HEIGHT WILL BE REDUCED BY THICKNESS OF CONCRETE FLOOR IF CONCRETE FLOORS ARE POURED. VISQUEEN VAPOR BARRIER IN ENERGY PERFORMER™ BUILDINGS CANNOT BE REMOVED! ALL DIMENSIONS ARE NOMINAL.

CUSTOMER COPY