



STATE OF IDAHO DEPARTMENT OF WATER RESOURCES

USE TYPEWRITER OR BALLPOINT PEN

WELL DRILLER'S REPORT
State law requires that this report be filed with the Director, Department of Water Resources within 30 days after the completion or abandonment of the well.

1. WELL OWNER NameElvin_Dewitt Address _5025	7. WATER LEVEL Static water level4 feet below land surface. Flowing? _ Yes _ Ø No G.P.M. flow Artesian closed-in pressure p.s.i. Controlled by: _ Valve Cap _ Plug Temperature 60_ °F. Quality Describe artesian or temperature zones below. 8. WELL TEST DATA _ Pump _ Bailer _ XX Air _ Other Discherge G.P.M.								
3. PROPOSED USE XX Domestic □ Irrigation □ Monitor □ Industrial ⊠ Stock □ Waste Disposal or Injection □ Other(specify type)	9. LITHOLOGIC LOG 808*						7-1 Water		
		From		Material				No	
4. METHOD DRILLED		0		Brown Clay Sand and Gravel			-	\vdash	
XX Rotary		18		Brown clay			XX		
☐ Cable ☐ Mud ☐ Other			14.	Brown Clay					
(backhoe, hydraulic, etc.)	-	-		-			-		
5. WELL CONSTRUCTION	1-	-	-				-		
Casing schedule: x3x Steel	-		-				-	\vdash	
Thickness Diameter From To 1.250 inches 6 inches + 1 feet 33 feet	-	-	-	-			+		
inches inches feet feet feet inches feet feet feet feet feet feet feet fe									
Was casing drive shoe used? ¾¾ Yes □ No									
Was a packer or seal used? ☐ Yes ☑ No	-				RECEI	VED	-	-	
Perforated? XX Yes □ No	REGILIA					+-	\vdash		
How perforated? ☐ Factory ☐ Knife XX Torch ☐ Gun Size of perforation? 1/8 inches by 5 inches	NOV 2 9 1593					1593			
500 Number 25 From 3 3					Dopardment of the Control of the Con				
periorationsreetreet						+	\vdash		
perforationsfeetfeetfeet									
Well screen installed? ☐ Yes XX No									
Manufacturer Type	-	-					+	\vdash	
Top Packer or Headpipe	-	-		-					
Bottom of Tailpipe									
Diameter Slot size Set from feet to feet	_						-	-	
Diameter Slot size Set from feet to feet	-	-						-	
Gravel packed? Yes No Size of gravel				RECEIVED					
1001 0					NOU 2 2 MAS				
Surface seal depth1.8_ Material used in seal: Cement grout	-		-		NOV 2 2 1993		+	\vdash	
		7.0	1	0 7	WESTERN REGION				
☐ Temp. surface casing ② Overbore to seal depth				-					
Method of joining casing: ☐ Threaded x3x Welded	-	-	B 0	9 10	IOE				
☐ Solvent Weld ☐ Cernented between strata	10.				•••			- 1	
Describe access port		Work s	started	9-	10-93 finished	9-10	-93	_	
6. LOCATION OF WELL	11.	DRILL	ER'S.C	ERI	IFICATION ,				
Sketch map location must agree with written location.	I/We certify that all minimum well construction standards were								
Subdivision Name	and the state of t								
	1	Firm 6	ED .		AMID A PUMP CO.	No. 44	5		
W Lot No. Block No.			Pa	. 11	TE IDAHO 83061	11-10		3	
County Gem	Firm National BOAHO 85065 Date 11-19-93								
Address of Well Site 2800 Bishop Rd. Emmitt		Signed by Drilling Supervisor							
(give at least name of road)				and	0. 9 90	n			
SE 1/4 NE 1/4 Sec. 3 R. 3 E O or W XX	(Operator) (It different than the Drilling Supervisor)								