NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

(Please type or print)

CFD C 1070

(Do not write above this line)

Klam

State Well No. 345/7E-34d

State Permit No.

TER RECOUR	CES DEPT 140		
(1) OWNER:	F((19) LOCATION OF WELL:		
Name Victor he Creed	County Klamath Driller's well number		
Address RO Box 451	15/1 , 55 , and 30 - 74 - 75		
Chiloguin Ove. 97624	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /9/		
Rotary	Static level 23 ft. below land surface. Date 7/21/78		
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	11-11-0		
CASING INSTALLED: Threaded Welded Welded M	(12) WELL LOG: Diameter of well below casing // Depth drilled //3 ft. Depth of completed well //3 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	m and aquifer r	anatratad
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL	From To	swl
Size of perforations in. by in.	Top Soil	0 2	
perforations from ft. to ft.	Harry Brown Clay	2 19	
perforations from ft. to ft.	Bandy Drown Clay	19 34	<u> </u>
perforations from ft. to ft.	Dive Clary	34 60	
(7) SCREENS: Well screen installed? Yes X No	Blue Clay	60 63	
Manufacturer's Name	Sauch Blie Clay	100 113	221
Type Model No	Bleck Sand	113	277
Diam. Slot size Set from ft. to ft.			a
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	-		
Was a pump test made? [] Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " " " " " " " " " " " " " " " " " "	-		
<u>п</u> п п п п п п п п п п п п п п п п п п			
Bailer test 30 gal./min. with /2 ft. drawdown after / hrs.			
Artesian flow g.p.m.			
perature of water 53° Depth artesian flow encountered ft.	Work started 9/12/1/8 19 7 Complete	a 9/21	1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/21	1978
Well seal—Material used Cemein	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief	above are true	e to my
Diameter of well bore below seal in.	[Signed] / (Drilling Machine Operator) Date 1/22, 19/7		
Number of sacks of cement used in well seal sacks How was cement grout placed? Poured	Drilling Machine Operator's License No		
was cement grout placed?	Driving Machine Operator's License No		
	Water Well Contractor's Certification:	-	-
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief Name (1,236x Chance (1)x 1,21 - Dx 1,44		
Did any strata contain unusable water2 Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address ROBOX 405 Keno Ove 97627		
Method of sealing strata off	[Signed] Mayer W. Chancellor		
Was well gravel packed? [] Yes X No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 62.3 Date	1/22	., 1978