

State of Oregon  
WATER WELL REPORT (as required by ORS 537.765)

Page 1 of 2

State Well ID L63824  
Start Card # 157221

(1) OWNER: Well No. 2236  
Name TERRA FIRMA PARTNERS LLC  
Address POB 601  
City AMITY St OR Zip 97101

(2) TYPE OF WORK: NEW WELL

(3) DRILL METHOD: ROTARY AIR

(4) PROPOSED USE: DOMESTIC

(5) BORE HOLE CONSTRUCTION:

Special Construction Approval NO Depth of Compl. Well 531 ft  
Explosives used NO Type Amount

HOLE		SEAL			
Diam.	From To	Material	From To	Amount	
10	0 50	BENTONITE CHIP	0 50	33	SAX
6	50 531				

Seal placement method POURED/PROBED

Backfill: from \_\_\_ ft to \_\_\_ ft Material  
Gravel: from \_\_\_ ft to \_\_\_ ft Size

(6) CASING/LINER:

	Diam.	From	To	Gauge	Material	Connection
Casing	6	+2	50	.25	STEEL	WELDED

	Diam.	From	To	SDR	Material	Connection
Liner	4	0	531	SDR26	PLASTIC	WELDED

Final Location of shoe(s) 50

(7) PERFORATIONS/SCREENS:

[X] Perf. Method ELECTRIC SAW

[ ] Screens Type Material

From	To	Slot Size	Number	Diam.	Size	Casing/liner
491	511	.1X7"	38			LINER
521	531	.1X7"	18			LINER

(8) WELL TESTS: Minimum testing time is 1 hour

Test type BAILER

Yield GPM	Draw-down	Drill stem at	Time
35		531	1 hr.
35		515	1

Temperature of water 53F Depth Artesian Flow Found

Was water analysis done? YES By whom BWD

Reason for water not suitable for use

Depth of strata

(9) LOCATION OF WELL by legal description:

County YAMHILL Lat. ' ' ' ' Long. ' ' ' '  
Township 5 S Range 4 W WM.  
Section 25 NW 1/4 NW 1/4  
Tax Lot 2301 Lot Block Subdivision  
Street Address of Well (or nearest Address)  
NYA, SE CHERRY BLOSSOM LN AMITY, OR

(10) STATIC WATER LEVEL:

266 ft. below land surface. Date 08/29/03

Artesian pressure \_\_\_ lb per square in. Date

(11) WATER BEARING ZONES:

Depth at which water was first found	455	Est Flow Rate	SWL
From	To		
455	511	35	266

(12) WELL LOG:

Material	Ground elevation		SWL
	From	To	
TOP SOIL	0	2	
SOIL W/COBBLES AND BOULDERS	2	8	
BASALT, DECAYED BROWN	8	22	
BASALT, HARD GRAY	22	27	
BASALT, DECAYED BROWN	27	31	
BASALT, HARD GRAY	31	95	
BASALT, MEDIUM GRAY W/SOME BROWN	95	101	
BASALT, MEDIUM GRAY	101	118	
BASALT, VERY HARD GRAY	118	212	
BASALT, MEDIUM GRAY W/OCC DECAY	212	220	
BASALT, VERY HARD GRAY	220	381	
BASALT, MEDIUM GRAY	381	399	
BASALT, VERY HARD GRAY	399	455	
BASALT, MEDIUM GRAY, OCC FRACTURES	455	511	266
BASALT, VERY HARD GRAY	511	531	

DAVE PAYSINGER, BLUE WATER DRILLING CO.

Date started 08/21/03

Completed 08/29/03

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to my best knowledge and belief.

Signed \_\_\_\_\_ WWC Number \_\_\_\_\_  
Date \_\_\_\_\_

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.

Signed *David M. Paysinger* WWC Number 1438  
Date 08/29/03

RECEIVED  
SEP 24 2003  
WATER RESOURCES DEPT  
SALEM, OREGON