STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

HECEIV	ED 415 (START CARD)	85/5w/16ac

(as required by ORS 557.765)	(Other One) "			
(1) OWNER: Well Number:	(9) LOCATION OF WELL by legal description:			
Address 3930 MINTLETUE AND HESIDA	County Pouk Latitude Longitude			
City Daylers State ORECATION STATE	Township S Nor S. Range 50 Eor W. WM.			
(2) TYPE OF WORK:	Tax Lot Lot Block Subdjvision			
□ New Well □ Deepen ■ Recondition □ Abandon	Street Address of Well (or nearest address)			
(3) DRILL METHOD M/P				
Rotary Air Rotary Mud Cable	(10) STATIC WATER LEVEL:			
Other	ft. below land surface. Date 2-15-92			
(4) PROPOSED USE: Domestic	Artesian pressure lb. per square inch. Date			
Thermal Injection Other Industrial Irrigation	(11) WATER BEARING ZONES:			
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found			
ipecial Construction approval Yes No Depth of Completed Well ft.	From To Estimated Flow Rate SWL			
Yes No U Market Amount Amount Market Amount Market	SEE WELL LOGS DATED			
HOLE SEAL Amount	Aug, 12,1979 9 007, 19,1982			
Diameter From To Material From To Sacks or pounds				
	(12) WELL LOG: Ground elevation			
	Material From To SWL			
	, which is a similar to similar t			
How was seal placed: Method	PULLED RIMP & OLD			
Other	4 PNC LINEK. RAN DELLE RICE			
Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel	TO BOTTOM OF WELL, ALL TROW TESTED WELL @ 15 gAM			
(6) CASING/LINER:	INSTALLED NEW 4" P.CC. LINCE			
Diameter From To Gauge Steel Plastic Welded Threaded	WITH NEW PACKER INSTALL (TD)			
Casing:	AT 65, REMSTALLED PUMP			
	AND CHOROLATED WELL.			
	CASING OR SETAL			
Liner: 4200 5 220 0	CITSING DIE SEITE			
Final location of shoe(s)				
(7) PERFORATIONS/SCREENS:				
Perforations Method SKILL SAW				
Screens Type Material				
Slot Tele/pipe From To size Number Diameter size Casing Liner				
16 0 015 4 × 4 30				
	Date started 1-11 -92 Completed 1-0992			
	(unbonded) Water Well Constructor Certification:			
(8) WELL TESTS: Minimum testing time is 1 hour	I certify that the work I performed on the construction, alteration, or			
□ Pump □ Bailer ♣ Air □ Artesian	abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best			
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.			
15apm 140 220 1hr.	WWC Number			
	Signed Date			
	(bonded) Water Well Constructor Certification: 'I accept responsibility for the construction, alteration, or abandonment			
Temperature of water Depth Artesian Flow Found Was a water analysis done?	work performed on this well during the construction dates reported above. all			
Was a water analysis done?	work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and			
Salty Muddy Odor Colored Other CONTAMINATED	belief. O WWC Number 1278			
Depth of strata: 33' - abut /2 gra ve'a Signed work of Date 2-8-92				

WATER WELL REPORT STATE OF OREGON

RECEIVED

RECEIVED

OCT 19 1982

WATER RESOURCES DEP

WATER RESOURCES DEPT

State Well No.	8s/5w-16
State Demnit No	

5r 1	SALEM, OREGON Ceepened
(1) OWNER:	(10) LOCATION, OF WELL:
Name Ken Dorman	County Polk Driller's well number
Address 39-30 Mistostae, Rd.	X 4 4 Section / 7 T. S S R. 5 W W.M.
City Dallas State R 97338	Tax Lot # Lot Blk Subdivision
	Address at well location:
(2) TYPE OF WORK (check):	
New Well □ Deepening Reconditioning □ Abandon □	(11) WARRED LEWIS CO. 14 1 1
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Air Driven Domestic Industrial Municipal	Static level 8 () ft. below land surface. Date 8 - 18
Rotary Mud	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic	Depth drilled /35 ft. Depth of completed well 220 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
	for each change of formation. Report each change in position of Static Water Level
	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
# "Diam from 304 ft. to 220 ft. Gauge	Claystone - some 85 220
(6) PERFORATIONS: Perforated? Sees I No	hard streaks all
Type of perforator used Skul Sau	the way down
Size of perforations Y & in. by 6 in.	
196 perforations from 24 ft. to 220 ft.	
perforations from ft. to ft.	
perforations from	
(7) SCREENS: Well screen installed? Yes	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water level is levered	
(8) WELL TESTS: below static level compared to the property of the property	
Wes a pump test made? ☐ Yes 🔼 No If yes, by whom?	
i: gal./min. with ft. drawdown after hrs.	
11 " " "	
Air test 15 gal./min. with drill stem at 2/9 ft. / hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 8-18 1982 Completed 8-26 1982
(9) CONSTRUCTION: Special standards: Yes No	Date well drilling machine moved off of well 8-26 19 82
Well seal—Material used Clment onout /	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal,in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Tack Medican Date 0 70,19
Number of sacks of cement used in well seal	Drilling Machine Operator's License No
How was cement grout placed?	The special of the state of the
gressure Grouted	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name DICKERSON WELL DRILLING
Was a drive shoe used?	1 Person firm or corporation), Road (Type or print)
Did any strata contain unusable water? Yes Yes Yes Yes Yes	Address
Type of Water? depth of strata Method of sealing strata off	[Signed] Janl Lluckorain
Was well gravel packed? Yes V No Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No. 63.7Date
	L

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT AUG 1 2 1974 STATE OF OREGON

State Well No. 85/5W-16ac

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

Gravel placed from _____ ft. to _____ ft.

(Please type or print) STATE ENGINEER
State Permit No. (Do not write above this liSALEM, OREGON

(10) LOCATION OF WELL: (1) OWNER: Driller's well number SW 14 NE 14 Section Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [Reconditioning [Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Rotary Driven 🗆 Domestic Industrial | Municipal | Static level ft. below land surface. Date Cable Jetted 🛚 Irrigation Test Well Other Dug Bored | Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [(12)WELL LOG: Diameter of well below casing ft. to 36.5 ft. Gage Depth drilled ft. Depth of completed well ..." Diam. from Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes No. Type of perforator used SWL in. by Size of perforations perforations from ft. to perforations fromperforations from (7) SCREENS: Well screen installed?

Yes Manufacturer's Name Diam. Slot size Set from Diam. Slot size Set from Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made?
Yes No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. gal./min. with ft. drawdown after 2 hrs. g.p.m. perature of water 5 / Depth artesian flow encountered 1977 Completed Date well drilling machine moved off of well (9) CONSTRUCTION Drilling Machine Operator's Certification: Well seal-Material used .. This well was constructed under my direct supervision. Well sealed from land surface to ... 3/ Materials used and information reported above are true to my best knowledge and belief Diameter of well bore to bottom of seal Diameter of well bore below seal [Signed] (Drilling Machine Operator) Number of sacks of cement used in well seal . Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal .. Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge, and belief. Was a drive shoe used?

Yes No Plugs Size: location Did any strata contain unusable water?

Yes

No Type of water? depth of strata Address . Method of sealing strata off Was well gravel packed? ☐ Yes ☐ No Size of gravel: Contractor's License No. 4.57 Date