## **Attention Owner:**

Confidentiality Privilege Notice on reverse side of owner's copy.

## **Texas Department of License and Regulation**

Water Well Driller/Pump Installer Program
P.O. Box 12157 Austin, Texas 78711 (512)463-7880 FAX (512)463-8616 Toll free (800)803-9202

Email address: water.well@license.state.tx.us WELL REPORT

This form must be completed and filed with the department and owner within 60 days upon completion of the well.

MONANAR	A. W		inuriko Arino	ny As	งน์ เนอร์	Amon	igyAttA			ŧ.,		
Name	Address						Argumentana (117 feliculate allellas (mar) y ban	State	Zip	Zip		
Keith Rogers	Route 1 Box 219			944	Evant			TX	. 76	76525		
WANTED ON THE WAY												
County	Physical Addr	ess		City	. 8. 8.	0.000		State	Zip	(-144		
Hamilton	Route 1	Box 219	N		Evan	t		TX	7652	25		
3) Type of Work Lat. 31.31.			.26 Long			98.16.64			Grid# 41-30-9			
New Well Reconditioning	4) Propose	d Use (chec	k) 🔲 Monit	Monitor Environmental Soil E			Boring 🚾 D	omestic	5)	NT		
Replacement Deepening	Industrial Irrigation Injection				Public St	upply 🔲	De-watering [	Testwell				
41	Rig Supply If Public Supply wi						tted? 🔲 Ye	s 🗖 No				
6) Drilling Date					7) Drilling Method (check) Driven				x			
Started 1 / 3 / 01	Dia.(in)	From (ft)	From (ft) To (ft)		2 Air	Rotary 🖵	Mud Rotary	Bored				
	8	0 . 10			Air Hammer Cable Tool Letted							
Completed 1 / 5 / 01	61/4	10			Other			effect an	vers of			
V 1849.	- 42		- 330		1							
formation material						8) Borehole Completion						
			Table 1 and			Under-reamed Gravel Packed Other						
0 10 top soil & c	1				vel Packed	give the interva	I from ft. to ft.		ft.			
0,	10 26 gray shale 26 85 gray lime & shale			. "			Pipe, and	Well Screen Data				
85 96 sandy sale & soapstone			Var.			New	Steel, Plastic		Setting (ft)	Gage		
96 112 sand & sandstone 113 125 broken sand & shale						Or Used	Perf., Slotte Screen Mfg	a, etc	From To	Casing Screen		
125 l35 marley lime			1			new	SDR 17		0 490			
135 280 gray lime w/ shale streaks						new		casing	490 530	1/8"		
280 314 broken lime 314 325 sandy shale	King and the second				new	SILLILIE	casing	490.530	1/8			
325 351 green shale & sandstone												
351 370 brown lime & red sandstone 370 410 hard brown lime				-	0) C-			, :		1		
410 420 brown lime & pink shale			25 5		9) Cementing Data Cementing from 10 ft to 11 ft #of sacks used 2							
420 428 red & green shale			essary)			Cementing from 0 - ft. to 11 ft. #of sacks used 2 100 ft. to 150 ft. #of sacks used 5						
428 480 sandstone, shale w/ sand streaks essary) 480 530 sandstone & sand					Method Used Doureed Cementing By driller							
Casing jen in wen. Centent/Demonite praced in wen:					Distance	e to septic s	ystem field or o	other concentrated contamination 100 ft.				
From (ft) To (ft) From (		o (ft)	Sacks use	d	Method	of verificat	on of above di	stance				
					10) Su	rface Co	mpletion					
					☐ Specified Surface Slab Installed							
14) Type Pump					Ø Specified Surface Sleeve Installed ⊂							
☐ Turbine ☐ Jet					☐ Approved Alternative Procedure Used							
Other												
Depth to pump bowls, cylinder, jet etc., 480 ft.  15) Water Test					11) Water Level  Static level_417 ft. below Date 1 / 5 / 01							
Typetest Pump Bailer Detted Estimated  Yield:gpm with 40 ft. drawdown afterhrs.					Artesian Flow gpm. Date /							
16) Water Quality					12) Packers Type							
Did you knowingly penetrate a strata which contain undesirable constituents.  Q YES  NO If yes, did you submit a REPORT OF UNDESIRABLE WATER					2 shafe-catcher 150							
Type of water Depth of Strata												
Was a chemical analysis made Yes A No						CILE DIGITO DESCRIPTION OF STATE OF STA						
Company or individual's Name (type or print)  Dalton Drill:						& Ser	VICON S	hale-cate Lig No. 3	2850WPK	7		
Addressp O Box 208 City Hamilton State TX Zip 765								1				
TO THE PARTY OF TH									,,,,,			
Signature of ba		/		Sign	ature		Cusas		1			